

NLS-FR40 Series

Desktop Barcode Scanner



The FR40 series desktop barcode scanner is capable of reading 1D/2D barcodes printed on paper or displayed on LCD screen and supports RS-232 and USB interfaces. Delivering superior performance and outstanding durability at an affordable price, this scanner provides an ideal solution for supermarkets, shopping malls, warehouses and other environments.

Features

- Demonstrates speedy scanning and accurate decoding on moving barcodes, including 1D, 2D and PDF417.
- Handheld and hands-free modes: Scan bulky items continuously without the need for unnecessary heavy lifting by checkout personnel.
- Omnidirectional scanning improves productivity by eliminating the need to align scanner and barcode.
- Unsurpassed readability on barcodes on the screen of smartphone or tablet using auto-brightness.
- Supports RS-232/USB interfaces.

Depth of Field

Symbology	Barcode Density	Depth of Field (mm)
Code 39	5mil	10~100
UPC-A	13mil	0~250
PDF417	6.67mil	0~80
Data Matrix	10mil	10~90
QR	15mil	10~150

Specifications

Performance

Image Sensor	CMOS	
Pixels	752x480	
Symbologies	2D	PDF417, QR Code (Model 1/2), Data Matrix (ECC200, ECC000, 050, 080, 100, 140), Aztec, Maxicode, etc.
	1D	Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN, Code 93, UCC/EAN-128, GS1 Databar, etc.
Precision	≥ 5mil	
Scan Angle**	Pitch	±60° @ 0° Roll and 0° Skew
	Roll	360° @ 0° Pitch and 0° Skew
	Skew	±55° @ 0° Roll and 0° Pitch

Motion Tolerance 2m/s

Minimum Symbol Contrast 25%

Interface RS-232, USB

Physical

Dimensions (L x W x H) 83x81x148mm

Weight 292g

Notification Beep, LED

Power Adaptor Output: DC 5V, 1.5A Input: AC 100 ~ 240V, 50~60Hz

Current **Operating Current** 350mA

Standby Current 70mA

Environmental

Operating Temperature -20°C ~50°C

Storage Temperature -40°C ~ 70°C

Humidity 5% ~ 95% (non-condensing)

ESD ±8KV (Contact discharge); ±14KV(Air discharge)

Drop 1.2m

Sealing IP50

Certifications

FCC Part15 Class B, CE EMC Class B

**Test conditions:

Code39, 3 Bytes; Resolution=10mil; W:N= 3:1; PCS=0.8; Barcode Height=11mm; Scan Distance=120mm; T=23°C; Illumination=200 LUX

Contact Us

Newland China

+86-400-608-0591

marketing@nlscan.com

Newland Europe

+31(0)-345-87-0033

info@newland-id.com

Newland Taiwan

+886-2-7731-5388

info@newland-id.com.tw

Newland North America

+1-510-490-3888

info@newlandna.com

www.nlscan.com

Specifications are subject to change without notice.

V1.0.0

